

PaxTower 1T - 53511

Professional tower system available in modular packs to build the tower up to 5.6m platform height with quick and safe assembly - 2m build intervals between each tower size. This Through the Trapdoor (3T) tower fully complies to the latest EN 1004-1 safety standard.



Product description

- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42794) to allow for height adjustment.
- Stile and rung diameter 45 mm.



Product features

Claw type automatic	Fits through doorways Yes	Height-adjustable castors: No	Overall height 1.65 m	Platform height 0.55 m



Platform length	Platform length	Platform size	Platform width	Rung diameter
1.8 m	1.8 m	0,6m x 1,8m	0.6 m	45 mm
Scaffolding class	Standards	Stile diameter	Transport dimensions	Warranty
3 (= 200 kg/m²)	EN 1004-1	45 mm	1.950 mm x 750 mm x 400 mm	10 years
Weight	Wheel diameter	Width scaffolding	Working height	
38.3 kg	125 mm	0.72 m	2.55 m	