

## PaxTower 1T - 53513

Professional tower system available in modular packs to build the tower up to 5.6m platform height with quick and safe assembly - 2m build intervals between each tower size. This Through the Trapdoor (3T) tower fully complies to the latest EN 1004-1 safety standard.

### Product description

- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m<sup>2</sup>) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42794) to allow for height adjustment.
- Stile and rung diameter 45 mm.



### Product features

Claw type	Fits through doorways	Height-adjustable castors:	Overall height	Platform height
<b>automatic</b>	<b>Yes</b>	<b>No</b>	<b>3.65 m</b>	<b>2.55 m</b>

Platform length <b>1.8 m</b>	Platform length <b>1.8 m</b>	Platform size <b>0,6m × 1,8m</b>	Platform width <b>0.6 m</b>	Rung diameter <b>45 mm</b>
Scaffolding class <b>3 (= 200 kg/m²)</b>	Standards <b>EN 1004-1</b>	Stile diameter <b>45 mm</b>	Transport dimensions <b>2.150 mm × 750 mm × 750 mm</b>	Warranty <b>10 years</b>
Weight <b>78 kg</b>	Wheel diameter <b>125 mm</b>	Width scaffolding <b>0.72 m</b>	Working height <b>4.55 m</b>	