

PaxTower S-PLUS 1T - 53522

The handy 1-click folding scaffold unit for discerning skilled workers, featuring the S-PLUS railing for greater safety during assembly and disassembly.

Product description

- Safer and quicker assembly and dismantling due to advanced guardrails and platforms at intervals of 2 m.
- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42794) to allow for height adjustment.
- Stile and rung diameter 45 mm.



Product features

Claw type	automatic
Fits through doorways	Yes



Height-adjustable castors:	No
Overall height	2.65 m
Platform height	1.55 m
Platform length	1.8 m
Platform length	1.8 m
Platform size	0,6m × 1,8m
Platform width	0.6 m
Rung diameter	45 mm
Scaffolding class	3 (= 200 kg/m ²)
Standards	EN 1004-1
Stile diameter	45 mm
Transport dimensions	2.150 mm × 750 mm × 700 mm
Warranty	10 years
Weight	71.4 kg
Wheel diameter	125 mm
Width scaffolding	0.72 m
Working height	3.55 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/7/2026

Subject to change or error.