DATA SHEET

PaxTower S-PLUS 1T - 53524

The handy 1-click folding scaffold unit for discerning skilled workers, featuring the S-PLUS railing for greater safety during assembly and disassembly.















PRODUCT DESCRIPTION

- Safer and quicker assembly and dismantling due to advanced guardrails and platforms at intervals of 2 m.
- One-piece fold out snap-frame with simple, one-handed lock and release operation, for quick and easy set up.
- Innovative toe board system with no clips – removes the need for toe board clips reducing the amount of loose components.
- Smooth slot-in spigots to prevent tilting when the end frames join together.
- Scaffolding length: 1.80 m; scaffolding width: 0.72 m.
- Scaffolding Category 3 (load capacity of up to 200 kg/m²) according to the new EN 1004.
- 125 mm swivel castors with brake; the castors can be fitted with castor adapters (order no. 42794) to allow for height adjustment.
- Stile and rung diameter 45 mm.

PRODUCT FEATURES

Property	Value
Claw type	automatic
Fits through doorways	Yes
Height-adjustable castors:	No
Overall height	4.65 m

Property	Value
Platform height	3.55 m
Platform length	1.8 m
Platform length	1.8 m
Platform size	0,6m × 1,8m
Platform width	0.6 m
Rung diameter	45 mm
Scaffolding class	3 (= 200 kg/m²)
Standards	EN 1004-1
Stile diameter	45 mm
Transport dimensions	2.150 mm × 750 mm × 950 mm
Warranty	10 years
Weight	108 kg
Wheel diameter	125 mm
Width scaffolding	0.72 m
Working height	5.55 m

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/7/2026
Subject to change or error.