

# Variomaster T - 53794

For quick use and safe standing: folds to compact size and is quickly set up.

## Product description

- For quick use and safe standing: folds to compact size and is quickly set up.
- Height can be effortlessly adjusted by just one person due to the self-locking mechanism similar to a push-up ladder.
- Can be easily folded to a compact size for transport and storage.
- Swing-out stabilisers with sturdy height adjusters for stability and for levelling out uneven floor/ground surfaces.
- Large-area work platform 0.50 x 1.95 m or 0.60 x 2.50 m.
- Peripheral railings for maximum safety.
- Simple height adjustment according to the self-locking push-up ladder principle, allowing you to reach different heights with only one work platform.
- Height adjustment can be operated by one person.
- Easily collapsible for transport and storage.
- Highly mobile and able to pass through doors when erected and collapsed thanks to rollers (Order No. 53794).
- No ballast weights are required for indoor use.
- Two sizes with height adjustment from 1.25 m to 2.46 m or 1.81 m to 3.58 m platform height.
- Scaffolding category 3 (can be loaded up to 200 kg/



m<sup>2</sup>) according to DIN EN 1 004.

## Product features

Footpoint, stabiliser rod extended L x W <b>1,9m × 2,3 m</b>	Footpoint, stabiliser rod retracted L x W <b>0,8m × 2,3 m</b>	Guardrail height <b>1 m</b>	Load capacity <b>max. 300 kg</b>	Overall height <b>2,31m - 3,52m</b>
Overall height <b>2.31 m</b>	Platform height <b>1,25m - 2,46m</b>	Platform length <b>2.5 m</b>	Platform material <b>glued plywood panel</b>	Platform width <b>0.6 m</b>
Transport dimensions <b>2.290 mm × 780 mm × 750 mm</b>	Tread depth <b>30 mm</b>	Warranty <b>10 years</b>	Weight <b>92 kg</b>	Width extended <b>2.3 m</b>
Width retracted <b>2.3 m</b>	Working height <b>4.5 m</b>	closed length <b>0.8 m</b>	extended length <b>1.9 m</b>	