



Y-Case and SanPack

Transport and storage container for military applications.

Product description

- Casing joint welded throughout.
- Extra strong 1.5 mm sheet
- Sturdy base, edge and lid profile.
- Hinged lid with all-round seal.
- Sturdy cast-iron stacking corners on the lid
- Stacking feet on the base with attachment bores on inside and outside.
- Waterproof down to the bottom edge of the drop handle thanks to a silicone seal on the inside of the base.
- Snap fasteners with protection against bursting open.
- Ergonomic & durable C. fasteners for at least 20,000 operating cycles.
- Lid loose in the case of B 40.1 Y, B 40.2 Y and B 40.4 Y.
- IP 54 protection class according to DIN EN 60 529 : 1992



Hints and special features

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

UN approval for the transportation of hazardous goods possible at additional charge.

Product variants

	45051	45050	45052	45055	45053	45054
Internal dimensions L x W x H	380 mm × 265 mm × 220 mm	570 mm × 380 mm × 220 mm	570 mm × 380 mm × 466 mm	794 mm × 572 mm × 220 mm	794 mm × 572 mm × 466 mm	794 mm × 572 mm × 717 mm
Max. gross weight dangerous goods permission	25 kg	32 kg	46 kg	46 kg	76 kg	107 kg
Outside dimensions max. L x W x H	420 mm × 305 mm × 270 mm	615 mm × 420 mm × 270 mm	615 mm × 420 mm × 516 mm	835 mm × 615 mm × 270 mm	835 mm × 615 mm × 516 mm	835 mm × 615 mm × 761 mm
Version	B5.2 Y	B5 Y	B10 Y	B20.2 Y	B20 Y	B20.1 Y
Volume	22 l	47 l	100 l	99 l	211 l	325 l
Weight	4.2 kg	6.4 kg	7.6 kg	11.4 kg	13.8 kg	17 kg

	45058	45056	45057
Internal dimensions L x W x H	1.175 mm × 793 mm × 220 mm	1.175 mm × 793 mm × 465 mm	1.175 mm × 793 mm × 717 mm
Max. gross weight dangerous goods permission	75 kg	137 kg	200 kg
Outside dimensions max. L x W x H	1.215 mm × 833 mm × 270 mm	1.215 mm × 833 mm × 516 mm	1.215 mm × 833 mm × 761 mm
Version	B40.2 Y	B40 Y	B40.1 Y
Volume	205 l	433 l	668 l
Weight	18 kg	22 kg	25.7 kg

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/29/2026

Subject to change or error.