

Mitraset Classic 19" case

Enclosure for housing electronic devices in a 19-inch rack

Product description

- Protection against mechanical stresses such as shocks, impacts, and vibrations. Optional protection against electromagnetic interference.
- IP 65 rated
- Protection against environmental factors such as heat, moisture, moisture, and dust.
- For loads up to 100 kg. Higher loads must be evaluated on a case-by-case basis.
- 3–16 height units (HU), nominal depth (ND) 219–762 mm.
- Housings with nominal depths 219 mm, 350 mm and 480 mm can be stacked together.
- Elastically susp. anti-vibration frame.
- Stacking segments on housing top and bottom.
- Recesses on side walls for drop handles.
- Recess also suitable for accommodating protective pressure compensation valves and humidity indicator.
- Lid with toggle-action snap fasteners.
- ZARGES Comfort Handles for ergonomic handling.
- Fulfils the requirements of VG 95447.
- Tested according to AECTP standards.
- Tested according to MIL-STD-810.
- Significantly better shielding properties compared to plastic enclosures. If necessary, these can be further improved through special measures.



- Custom modifications are available.
- Made in Germany

Hints and special features

Also available as UN-approved hazardous goods packaging.

Comprehensive range of special fittings for many applications.

Product variants

	45702	45708	45714	45726	45720	45732
Installation height	3 HE/U	4 HE/U	5 HE/U	7 HE/U	6 HE/U	8 HE/U
Nominal depth	219 mm	219 mm	219 mm	219 mm	219 mm	219 mm
Outside dimensions max. L x W x H	303 mm x 534 mm x 214,5 mm	303 mm x 534 mm x 259 mm	303 mm x 534 mm x 303,5 mm	303 mm x 534 mm x 392,5 mm	303 mm x 534 mm x 348 mm	303 mm x 534 mm x 437 mm
Weight	6.6 kg	7 kg	7.3 kg	7.8 kg	7.5 kg	8.2 kg

	45738	45744	45750	45756	45704	45710
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	3 HE/U	4 HE/U
Nominal depth	219 mm	219 mm	219 mm	219 mm	350 mm	350 mm
Outside dimensions max. L x W x H	303 mm x 534 mm x 481,5 mm	303 mm x 534 mm x 526 mm	303 mm x 534 mm x 570,5 mm	303 mm x 534 mm x 615 mm	434 mm x 534 mm x 214,5 mm	434 mm x 534 mm x 259 mm
Weight	8.4 kg	8.6 kg	8.8 kg	9 kg	8.6 kg	9 kg

	45716	45722	45728	45734	45740	45746
Installation height	5 HE/U	6 HE/U	7 HE/U	8 HE/U	9 HE/U	10 HE/U
Nominal depth	350 mm	350 mm	350 mm	350 mm	350 mm	350 mm
Outside dimensions max. L x W x H	434 mm x 534 mm x 303,5 mm	434 mm x 534 mm x 348 mm	434 mm x 534 mm x 348 mm	434 mm x 534 mm x 437 mm	434 mm x 534 mm x 481,5 mm	434 mm x 534 mm x 526 mm
Weight	9.3 kg	9.6 kg	10 kg	10.3 kg	10.7 kg	11 kg

	45752	45758	45706	45712	45718	45724
Installation height	11 HE/U	12 HE/U	3 HE/U	4 HE/U	5 HE/U	6 HE/U
Nominal depth	350 mm	350 mm	480 mm	480 mm	480 mm	480 mm
Outside dimensions max. L x W x H	434 mm x 534 mm x 570,5 mm	434 mm x 534 mm x 615 mm	564 mm x 534 mm x 214,5 mm	564 mm x 534 mm x 259 mm	564 mm x 534 mm x 303,5 mm	564 mm x 534 mm x 348 mm
Weight	11.3 kg	11.6 kg	10.7 kg	11.1 kg	11.4 kg	11.9 kg

	45730	45736	45742	45748	45754	45760
Installation height	7 HE/U	8 HE/U	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Nominal depth	480 mm	480 mm	480 mm	480 mm	480 mm	480 mm
Outside dimensions max. L x W x H	564 mm x 534 mm x 392,5 mm	564 mm x 534 mm x 437 mm	564 mm x 534 mm x 481,5 mm	564 mm x 534 mm x 526 mm	564 mm x 534 mm x 570,5 mm	564 mm x 534 mm x 615 mm
Weight	12.2 kg	12.6 kg	13 kg	13.3 kg	13.7 kg	14.1 kg

	45803	45804	45805	45806	45807	45808
Installation height	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Nominal depth	610 mm	610 mm	610 mm	610 mm	610 mm	610 mm
Outside dimensions max. L x W x H	704 mm x 534 mm x 214,5 mm	704 mm x 534 mm x 259 mm	704 mm x 534 mm x 303,5 mm	704 mm x 534 mm x 348 mm	704 mm x 534 mm x 392,5 mm	704 mm x 534 mm x 437 mm
Weight	13.5 kg	14.1 kg	14.7 kg	15.2 kg	15.9 kg	16.6 kg

	45809	45810	45811	45812	45814	45816
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	14 HE/U	16 HE/U
Nominal depth	610 mm	610 mm	610 mm	610 mm	610 mm	610 mm
Outside dimensions max. L x W x H	704 mm x 534 mm x 481,5 mm	704 mm x 534 mm x 526 mm	704 mm x 534 mm x 570,5 mm	704 mm x 534 mm x 615 mm	704 mm x 534 mm x 704 mm	704 mm x 534 mm x 793 mm
Weight	17.1 kg	17.5 kg	24.7 kg	18.6 kg	19.9 kg	-

	45863	45864	45865	45866	45867	45868
Installation height	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Nominal depth	762 mm	762 mm	762 mm	762 mm	762 mm	762 mm
Outside dimensions max. L x W x H	856 mm x 534 mm x 214,5 mm	856 mm x 534 mm x 259 mm	856 mm x 534 mm x 303,5 mm	856 mm x 534 mm x 348 mm	856 mm x 534 mm x 392,5 mm	856 mm x 534 mm x 437 mm
Weight	16.2 kg	16.8 kg	17.4 kg	17.9 kg	18.6 kg	19.3 kg

	45869	45870	45871	45872	45874	45876
Installation height	9 HE/U	10 HE/U	11 HE/U	12 HE/U	14 HE/U	16 HE/U
Nominal depth	762 mm	762 mm	762 mm	762 mm	762 mm	762 mm
Outside dimensions max. L x W x H	856 mm x 534 mm x 481,5 mm	856 mm x 534 mm x 526 mm	856 mm x 534 mm x 570,5 mm	856 mm x 534 mm x 615 mm	856 mm x 534 mm x 704 mm	856 mm x 534 mm x 793 mm
Weight	19.8 kg	20.2 kg	20.8 kg	21.3 kg	22 kg	23.8 kg

	45878
Installation height	18 HE/U
Nominal depth	762 mm
Outside dimensions max. L x W x H	856 mm x 534 mm x 882 mm
Weight	25.6 kg

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/12/2026

Subject to change or error.