

Lid for Mitraset Racklite

19" housing

Product description

- Flexible stacking elements at the corners of the housing and lid. Units with the same nominal depth are stackable.
- Lid equipped with 4 locking catches.
- Lids stiffened with moulded sections.
- Protection rating IP 65 in accordance with DIN EN 60529 and IEC 34-5/529 as a result of welded casing and lid with all-round seal.
- Wide range of special lids available on request.



Product variants

| | 45933 | 45934 | 45935 | 45936 | 45937 | 45938 |
|-----------------------------------|---------------------------|-------------------------|---------------------------|-------------------------|---------------------------|-------------------------|
| Height lid | 3 HE/U | 4 HE/U | 5 HE/U | 6 HE/U | 7 HE/U | 8 HE/U |
| Outside dimensions max. L x W x H | 55 mm x 591 mm x 271,5 mm | 55 mm x 591 mm x 316 mm | 55 mm x 591 mm x 360,5 mm | 55 mm x 591 mm x 405 mm | 55 mm x 591 mm x 449,5 mm | 55 mm x 591 mm x 494 mm |
| Weight | 2.2 kg | 2.4 kg | 2.6 kg | 2.7 kg | 2.9 kg | 3.1 kg |

| | 45939 | 45940 | 45941 | 45942 |
|-----------------------------------|---------------------------|-------------------------|---------------------------|-------------------------|
| Height lid | 9 HE/U | 10 HE/U | 11 HE/U | 12 HE/U |
| Outside dimensions max. L x W x H | 55 mm x 591 mm x 538,5 mm | 55 mm x 591 mm x 583 mm | 55 mm x 591 mm x 627,5 mm | 55 mm x 591 mm x 672 mm |
| Weight | 3.3 kg | 3.4 kg | 3.6 kg | 3.8 kg |



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/26/2026

Subject to change or error.