ZARGES

DATA SHEET

# Mitraset Racklite Basic 19" housing

Enclosure for housing electronic devices in a 19-inch rack





## PRODUCT DESCRIPTION

- For mounting electronic devices in a 19-inch rack
- Variable designs with different depths and heights.
- Comprehensive range of special fittings for many applications.
- Protection rating IP 65 in accordance with DIN EN 60529 and IEC 34-5/529 as a result of welded casing and lid with all-round seal.
- The anti-vibration frame is connected to the housing via 8 rubber dampers and 2 earth straps.
- Stackable using stacking knobs and recesses.
- Items with same nominal depth are stackable.
- ZARGES Comfort Handles for ergonomic handling.
- ZARGES Comfort fastener for ergonomic operation and an extremely long service life.
- Snap fasteners with protection against bursting open.
- RF-tight version is available as special equipment.

## PRODUCT VARIANTS

| | 45943 | 45944 | 45945 | 45946 | 45947 | 45948 |
|---|---|---|---|---|---|---|
| Installation height | 3 HE/U | 4 HE/U | 5 HE/U | 6 HE/U | 7 HE/U | 8 HE/U |
| Nominal depth | 350 mm | 350 mm | 350 mm | 350 mm | 350 mm | 350 mm |
| Outside dimensions max. L x W x H | 456 mm × 568 mm × 226 mm | 456 mm × 568 mm × 270,5 mm | 456 mm × 568 mm × 315 mm | 456 mm × 568 mm × 359,5 mm | 456 mm × 568 mm × 404 mm | 456 mm × 568 mm × 448,5 mm |
| Weight | 7.7 kg | 8.3 kg | 8.7 kg | 9 kg | 9.3 kg | 9.6 kg |

| | 45949 | 45950 | 45951 | 45952 | 45953 | 45954 |
|---|---|---|---|---|---|---|
| Installation height | 9 HE/U | 10 HE/U | 11 HE/U | 12 HE/U | 3 HE/U | 4 HE/U |
| Nominal depth | 350 mm | 350 mm | 350 mm | 350 mm | 480 mm | 480 mm |
| Outside dimensions max. L x W x H | 456 mm × 568 mm × 493 mm | 456 mm × 568 mm × 537,5 mm | 456 mm × 568 mm × 582 mm | 456 mm × 568 mm × 626,5 mm | 586 mm × 568 mm × 226 mm | 586 mm × 568 mm × 270,5 mm |
| Weight | 10 kg | 10.3 kg | 10.6 kg | 11 kg | 9.1 kg | 9.8 kg |

| | 45955 | 45956 | 45957 | 45958 | 45959 | 45960 |
|---|---|---|---|---|---|---|
| Installation height | 5 HE/U | 6 HE/U | 7 HE/U | 8 HE/U | 9 HE/U | 10 HE/U |
| Nominal depth | 480 mm | 480 mm | 480 mm | 480 mm | 480 mm | 480 mm |
| Outside dimensions max. L x W x H | 586 mm × 568 mm × 315 mm | 586 mm × 568 mm × 359,5 mm | 586 mm × 568 mm × 404 mm | 586 mm × 568 mm × 448,5 mm | 586 mm × 568 mm × 493 mm | 586 mm × 568 mm × 537,5 mm |
| Weight | 10.2 kg | 10.5 kg | 10.5 kg | 11.3 kg | 11.7 kg | 12 kg |

| | 45961 | 45962 | 45963 | 45964 | 45965 | 45966 |
|---|---|---|---|---|---|---|
| Installation height | 11 HE/U | 12 HE/U | 3 HE/U | 4 HE/U | 5 HE/U | 6 HE/U |
| Nominal depth | 480 mm | 480 mm | 610 mm | 610 mm | 610 mm | 610 mm |
| Outside dimensions max. L x W x H | 586 mm × 568 mm × 582 mm | 586 mm × 568 mm × 626,5 mm | 716 mm × 568 mm × 226 mm | 716 mm × 568 mm × 270,5 mm | 716 mm × 568 mm × 315 mm | 716 mm × 568 mm × 359,5 mm |
| Weight | 12.4 kg | 12.8 kg | 10.4 kg | 11.1 kg | 11.5 kg | 11.9 kg |

| | 45967 | 45968 | 45969 | 45970 | 45971 | 45972 |
|---|---|---|---|---|---|---|
| Installation height | 7 HE/U | 8 HE/U | 9 HE/U | 10 HE/U | 11 HE/U | 12 HE/U |
| Nominal depth | 610 mm | 610 mm | 610 mm | 610 mm | 610 mm | 610 mm |
| Outside dimensions max. L x W x H | 716 mm × 568 mm × 404 mm | 716 mm × 568 mm × 448,5 mm | 716 mm × 568 mm × 493 mm | 716 mm × 568 mm × 537,5 mm | 716 mm × 568 mm × 582 mm | 716 mm × 568 mm × 626,5 mm |
| Weight | 12.3 kg | 12.8 kg | 13.2 kg | 13.6 kg | 14 kg | 14.4 kg |

| | 45973 | 45974 | 45975 | 45976 | 45977 | 45978 |
|---|---|---|---|---|---|---|
| Installation height | – | – | – | – | – | – |
| Nominal depth | – | – | – | – | – | – |
| Outside dimensions max. L x W x H | – | – | – | – | – | – |
| Weight | – | – | – | – | – | – |

| | 45979 | 45980 | 45981 | 45982 |
|---|---|---|---|---|
| Installation height | – | – | – | – |
| Nominal depth | – | – | – | – |
| Outside dimensions max. L x W x H | – | – | – | – |
| Weight | – | – | – | – |

## ACCESSORIES AND SPARE PARTS

### ACCESSORIES 1

**Lid for Mitraset Racklite Basic 19" housing**
SKU 45983

**ZARGES GMBH**
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/9/2026
Subject to change or error.