ZARGES

DATA SHEET

Lid for Mitraset Racklite Basic 19" housing

PRODUCT DESCRIPTION

- Protection rating IP 65 in accordance with DIN EN 60529 and IEC 34-5/529 as a result of welded casing and lid with all-round seal.
- Wide range of special lids available on request.
- Lids stiffened with moulded sections.
- Lid equipped with 4 locking catches.

PRODUCT VARIANTS

	45983	45984	45985	45986	45987	45988
Height lid	3 HE/U	4 HE/U	5 HE/U	6 HE/U	7 HE/U	8 HE/U
Outside dimensions max. L x W x H	40 mm × 568 mm × 226 mm	40 mm × 568 mm × 270,5 mm	40 mm × 568 mm × 315 mm	40 mm × 568 mm × 359,5 mm	40 mm × 568 mm × 404 mm	40 mm × 568 mm × 448,5 mm
Weight	1.8 kg	2 kg	2.2 kg	2.3 kg	2.5 kg	2.7 kg

	45989	45990	45991	45992
Height lid	9 HE/U	10 HE/U	11 HE/U	12 HE/U
Outside dimensions max. L x W x H	40 mm × 568 mm × 493 mm	40 mm × 568 mm × 537,5 mm	40 mm × 568 mm × 582 mm	40 mm × 568 mm × 626,5 mm
Weight	2.9 kg	3 kg	3.2 kg	3.4 kg

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/8/2026
Subject to change or error.