

# MultiTower S-PLUS 1T, 2,50

m

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.

## Product description

- The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.
- Scaffolding width: 0.75 m; scaffolding length: 2.50 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights ranging from 3.40 m to a maximum of 13.20 m can be achieved using standard components.
- Scaffolding Group 3 (strength up to 200 kg/m<sup>2</sup>) in accordance with DIN EN 1004-1.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



## Hints and special features

By adding the relevant S-PLUS single parts, this safer configuration can also be retrofitted to standard mobile scaffold towers with triangular stabilisers.

## Product features

Claw type	automatic
Height-adjustable castors:	Yes
Platform length	2.5 m
Platform length	2.5 m
Platform size	0,6m × 2,5m
Platform width	0.6 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m <sup>2</sup> )
Standards	EN 1004-1
Stile diameter	50 mm
Warranty	10 years
Wheel diameter	200 mm
Width scaffolding	0.75 m

## Product variants

	52226	52236	52246	52256	52266	52276
Overall height	2.65 m	3.75 m	4.6 m	5.7 m	6.55 m	7.65 m
Platform height	1.4 m	2.5 m	3.35 m	4.45 m	5.3 m	6.4 m
Transport dimensions	2.800 mm × 900 mm × 400 mm	2.800 mm × 900 mm × 500 mm	2.800 mm × 900 mm × 600 mm	2.800 mm × 900 mm × 700 mm	2.800 mm × 900 mm × 800 mm	2.800 mm × 900 mm × 900 mm
Weight	105.9 kg	132.5 kg	168.8 kg	182.8 kg	219.1 kg	233.1 kg
Working height	3.4 m	4.5 m	5.35 m	6.45 m	7.3 m	8.4 m



	52286	52296	52306	52316	52326
Overall height	8.5 m	9.65 m	10.45 m	11.6 m	12.45 m
Platform height	7.25 m	8.4 m	9.2 m	10.35 m	11.2 m
Transport dimensions	2.800 mm × 900 mm × 1.000 mm	2.800 mm × 900 mm × 1.100 mm	2.800 mm × 900 mm × 1.200 mm	2.800 mm × 900 mm × 1.300 mm	2.800 mm × 900 mm × 1.400 mm
Weight	277.8 kg	291.8 kg	328.1 kg	342.1 kg	378.4 kg
Working height	9.25 m	10.4 m	11.2 m	12.35 m	13.2 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/12/2026

Subject to change or error.