

# MultiTower S-PLUS 2T, 1,80

m

Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.

## Product description

- Maximum working area, safe and quick erection through advanced guardrail, low platform spacing and fewer single parts.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Scaffolding width: 1.35 m; scaffolding length: 1.80 m.
- Working heights ranging from 3.40 m to a maximum of 13.20 m can be achieved using standard components.
- Scaffolding Group 3 (strength up to 200 kg/m<sup>2</sup>) in accordance with DIN EN 1004-1.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



## Hints and special features

By adding the relevant S-PLUS single parts, this safer configuration can also be retrofitted to standard mobile scaffold towers with triangular stabilisers.

## Product features

Claw type	automatic
Height-adjustable castors:	Yes
Platform length	1.8 m
Platform length	1.8 m
Platform size	1,2m × 1,8m
Platform width	1.2 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m <sup>2</sup> )
Standards	EN 1004-1
Stile diameter	50 mm
Warranty	10 years
Wheel diameter	200 mm
Width scaffolding	1.35 m

## Product variants

	52425	52435	52445	52455	52465	52475
Overall height	2.65 m	3.75 m	4.6 m	5.7 m	6.55 m	7.65 m
Platform height	1.4 m	2.5 m	3.35 m	4.45 m	5.3 m	6.4 m
Transport dimensions	2.100 mm × 1.500 mm × 400 mm	2.100 mm × 1.500 mm × 500 mm	2.100 mm × 1.500 mm × 600 mm	2.100 mm × 1.500 mm × 700 mm	2.100 mm × 1.500 mm × 800 mm	2.100 mm × 1.500 mm × 900 mm
Weight	105.6 kg	140.7 kg	190.5 kg	197.1 kg	242.5 kg	248.5 kg
Working height	3.4 m	4.5 m	5.35 m	6.45 m	7.3 m	8.4 m



	52485	52495	52505	52515	52525
Overall height	8.5 m	9.65 m	10.45 m	11.6 m	12.45 m
Platform height	7.25 m	8.4 m	9.2 m	10.35 m	11.2 m
Transport dimensions	2.100 mm × 1.500 mm × 1.000 mm	2.100 mm × 1.500 mm × 1.100 mm	2.100 mm × 1.500 mm × 1.200 mm	2.100 mm × 1.500 mm × 1.300 mm	2.100 mm × 1.500 mm × 1.400 mm
Weight	293.9 kg	300.5 kg	345.9 kg	352.5 kg	397.9 kg
Working height	9.25 m	10.4 m	11.2 m	12.35 m	13.2 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 6/27/2026

Subject to change or error.