

CompactMaster S-PLUS 1T

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

Product description

- The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 0.85 m (to the outside edge of folding unit hinge); scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Scaffolding Group 3 (strength up to 200 kg/m²) in accordance with DIN EN 1004-1.
- Standard casters: 150 mm swivel castors with height adjustment (order no. 42755) for precise height adjustment down to the millimeter.



Product features

Claw type	automatic
Platform length	1.8 m
Platform length	1.8 m
Platform size	0,6m × 1,8m
Platform width	0.6 m
Rung diameter	50 mm



Scaffolding class	3 (= 200 kg/m ²)
Stile diameter	50 mm
Warranty	10 years
Width scaffolding	0.85 m

Product variants

	53300	53099	53121	53131	53141	53151
Height-adjustable castors:	No	Yes	Yes	Yes	Yes	Yes
Overall height	1.65 m	3 m	3.85 m	4.95 m	5.8 m	6.9 m
Platform height	0.95 m	1.75 m	2.6 m	3.7 m	4.55 m	5.65 m
Standards	–	EN 1004-1	EN 1004-1	EN 1004-1	EN 1004-1	EN 1004-1
Transport dimensions	1.900 mm × approx. 950 mm × approx. 480 mm	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm
Weight	35.8 kg	105.8 kg	123.6 kg	147.8 kg	165.6 kg	189.8 kg
Wheel diameter	125 mm	150 mm	150 mm	150 mm	150 mm	150 mm
Working height	2.95 m	3.75 m	4.6 m	5.7 m	6.55 m	7.65 m

	53161	53171	53181	53191	53101	53111
Height-adjustable castors:	Yes	Yes	Yes	Yes	Yes	Yes
Overall height	7.75 m	8.9 m	9.7 m	10.85 m	11.7 m	12.8 m
Platform height	6.5 m	7.6 m	8.4 m	9.6 m	10.4 m	11.55 m
Standards	EN 1004-1	EN 1004-1	EN 1004-1	EN 1004-1	EN 1004-1	EN 1004-1
Transport dimensions	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm
Weight	216 kg	231.8 kg	249.6 kg	273.8 kg	291.6 kg	315.8 kg
Wheel diameter	150 mm	150 mm	150 mm	150 mm	150 mm	150 mm
Working height	8.5 m	9.6 m	10.45 m	11.6 m	12.4 m	13.55 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/26/2026

Subject to change or error.