

CompactMaster S-PLUS 2T

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

Product description

- Scaffolding width: 0.85 m or 1.45 m (lower section incl. hinges); Scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding Group 3 (strength up to 200 kg/m²) in accordance with DIN EN 1004-1.
- Standard casters: 150 mm swivel castors with height adjustment (order no. 42755) for precise height adjustment down to the millimeter.



Product features

Claw type	automatic
Fits through doorways	No
Platform length	1.8 m
Platform length	1.8 m
Platform size	1,2m × 1,8m
Platform width	1.2 m
Rung diameter	50 mm
Scaffolding class	3 (= 200 kg/m ²)

Stile diameter	50 mm
Warranty	10 years
Width scaffolding	1.45 m

Product variants

	53400	53199	53221	53231	53241	53251
Height-adjustable castors:	No	Yes	Yes	Yes	Yes	Yes
Overall height	1.65 m	3 m	3.85 m	4.95 m	5.8 m	6.9 m
Platform height	0.95 m	1.75 m	2.6 m	3.7 m	4.55 m	5.65 m
Transport dimensions	0 mm × 0 mm × 0 mm	0 mm0 mm0 mm				
Weight	52.8 kg	108.1 kg	161.4 kg	189.4 kg	225 kg	250.7 kg
Wheel diameter	125 mm	150 mm	150 mm	150 mm	150 mm	150 mm
Working height	2.95 m	3.75 m	4.6 m	5.7 m	6.55 m	7.65 m

	53261	53271	53281	53291	53201	53211
Height-adjustable castors:	Yes	Yes	Yes	Yes	Yes	Yes
Overall height	7.75 m	8.9 m	9.7 m	10.85 m	11.7 m	12.8 m
Platform height	6.5 m	7.6 m	8.4 m	9.6 m	10.4 m	11.55 m
Transport dimensions	0 mm0 mm0 mm					
Weight	284 kg	312 kg	345.3 kg	373.3 kg	406.6 kg	434.6 kg
Wheel diameter	150 mm					
Working height	8.5 m	9.6 m	10.45 m	11.6 m	12.4 m	13.55 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.