

# Seventec L

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

## Product description

- The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.
- Smooth external stile surfaces that are comfortable to hold.
- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Outside width: 400 mm.
- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.



## Hints and special features

in accordance with DIN EN 131-1, order No. 40384

includes a stabiliser bar.

Complies with EN 131 Professional.

## Product features

Coating	Connection Stile-Rung	Load capacity	Material	Pitch rung/tread
---------	-----------------------	---------------	----------	------------------



natural	riveted	max. 150 kg	Aluminium	218 mm
Standards <b>EN 131 professional</b>	Stile depth <b>87 mm</b>	Tread depth <b>85 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>
certification-mark-pf <b>TÜV-SÜD</b>				

## Product variants

SKU <b>40378</b>	SKU <b>40380</b>	SKU <b>40382</b>
Number of treads <b>8</b>	Number of treads <b>10</b>	Number of treads <b>12</b>
Overall length <b>2.08 m</b>	Overall length <b>2.54 m</b>	Overall length <b>2.99 m</b>
Transport dimensions <b>2.090 mm × 400 mm × 90 mm</b>	Transport dimensions <b>2.550 mm × 400 mm × 90 mm</b>	Transport dimensions <b>3.010 mm × 400 mm × 90 mm</b>
Weight <b>5.8 kg</b>	Weight <b>7.2 kg</b>	Weight <b>8.5 kg</b>
Working height <b>3.05 m</b>	Working height <b>3.45 m</b>	Working height <b>3.9 m</b>
SKU <b>40384</b>		
Number of treads <b>14</b>		



ZARGES

Overall length

**3.42 m**

Transport dimensions

**3.470 mm × 400 mm × 90 mm**

Weight

**11.4 kg**

Wide crosspiece

**0.8 m**

Working height

**4.35 m**