

Seventec L

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

Product description

- The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.
- Smooth external stile surfaces that are comfortable to hold.
- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Outside width: 400 mm.
- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.



Hints and special features

in accordance with DIN EN 131-1, order No. 40384

includes a stabiliser bar.

Complies with EN 131 Professional.

Product features

Coating	natural
Connection Stile-Rung	riveted



Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	218 mm
Standards	EN 131 professional
Stile depth	87 mm
Tread depth	85 mm
Type rung/tread	serrated
Warranty	10 years
certification-mark-pf	TÜV-SÜD

Product variants

	40378	40380	40382	40384
Number of treads	8	10	12	14
Overall length	2.08 m	2.54 m	2.99 m	3.42 m
Transport dimensions	2.090 mm × 400 mm × 90 mm	2.550 mm × 400 mm × 90 mm	3.010 mm × 400 mm × 90 mm	3.470 mm × 400 mm × 90 mm
Weight	5.8 kg	7.2 kg	8.5 kg	11.4 kg
Wide crosspiece	-	-	-	0.8 m
Working height	3.05 m	3.45 m	3.9 m	4.35 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/29/2026

Subject to change or error.