

Stella L

The flexible solution for a wide variety of uses: extra-wide ladder is comfortable to use and safe to stand on.

Product description

- The flexible solution for a wide variety of uses: extra-wide ladder is comfortable to use and safe to stand on.
- Very light but still extremely stable.
- Also available as a shelf-ladder.
- Rung depth: 30 mm
- Outside width: 490 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium

Pitch rung/tread 270 mm

Standards EN 131 professional

Tread depth 30 mm

Type rung/tread serrated

Warranty 10 years

Product variants

	41511	41512	41513	41514	41515	41516
Number of rungs	6	8	10	12	14	16
Overall length	1.93 m	2.49 m	3.05 m	3.61 m	4.17 m	4.73 m
Stile depth	58 mm	58 mm	58 mm	58 mm	68 mm	68 mm
Transport dimensions	1.930 mm × approx. 500 mm × 60 mm	2.480 mm × approx. 500 mm × 60 mm	3.040 mm × approx. 500 mm × 60 mm	3.600 mm × approx. 500 mm × 60 mm	4.160 mm × approx. 500 mm × 65 mm	4.720 mm × approx. 500 mm × 70 mm
Weight	3.7 kg	4.7 kg	7.2 kg	8.1 kg	9.3 kg	10.5 kg
Wide crosspiece	–	–	0.8 m	0.89 m	0.99 m	0.99 m
Working height	2.8 m	3.35 m	3.9 m	4.4 m	4.95 m	5.5 m

	41510	41517	41518
Number of rungs	18	20	24
Overall length	5.29 m	5.86 m	6.98 m
Stile depth	73 mm	73 mm	85 mm
Transport dimensions	5.300 mm × approx. 500 mm × 75 mm	5.850 mm × approx. 500 mm × 75 mm	6.980 mm × approx. 500 mm × 85 mm
Weight	11.9 kg	13.2 kg	16 kg
Wide crosspiece	1.09 m	1.09 m	1.2 m
Working height	6.05 m	6.6 m	7.7 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/29/2026

Subject to change or error.