

## Strato DL

The inexpensive alternative for safe ascent and quick and flexible application.

### Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional



Tread depth 38 mm

Type rung/tread serrated

Warranty 10 years

### Product variants

	44808	44810	44812	44814	44816	44818
Number of rungs	8	10	12	14	16	18
Overall length	2.42 m	2.98 m	3.54 m	4.11 m	4.67 m	5.23 m
Stile depth	58 mm	58 mm	68 mm	73 mm	73 mm	73 mm
Transport dimensions	2.420 mm × 360 mm × 60 mm	2.980 mm × 360 mm × 60 mm	3.540 mm × 360 mm × 70 mm	4.110 mm × 360 mm × 75 mm	4.660 mm × 360 mm × 75 mm	5.220 mm × 360 mm × 75 mm
Weight	4.3 kg	5.3 kg	7.9 kg	9.2 kg	10.1 kg	11.2 kg
Wide crosspiece	–	–	0.79 m	0.79 m	0.89 m	0.89 m
Working height	3.3 m	3.85 m	4.4 m	4.9 m	5.45 m	6 m

	44819
Number of rungs	20
Overall length	5.9 m
Stile depth	73 mm
Transport dimensions	5.780 mm × 360 mm × 75 mm
Weight	12.4 kg
Wide crosspiece	0.99 m
Working height	6.55 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/22/2026

Subject to change or error.