

EFA L

The safety ladder for quick application in chemical or electrical environments.

Product description

- The safety ladder for quick application in chemical or electrical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Outside width: 420 mm - particularly stable.



Hints and special features

in accordance with DIN EN 131-1, order No. 41255

includes a stabiliser bar.

Complies with EN 131 Professional.

Product features

| | |
|---------------|-------------|
| Certification | TÜV-SÜD |
| Load capacity | max. 150 kg |

| | |
|------------------|--------------------------------|
| Material | Glass-fibre reinforced plastic |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Tread depth | 30 mm |
| Type rung/tread | serrated |
| Warranty | 10 years |

Product variants

| | 41251 | 41253 | 41255 |
|----------------------|---------------------------|---------------------------|---------------------------|
| Number of rungs | 6 | 10 | 14 |
| Overall length | 1.92 m | 2.993 m | 4.16 m |
| Stile depth | 58 mm | 58 mm | 73 mm |
| Transport dimensions | 1.924 mm × 430 mm × 70 mm | 3.044 mm × 430 mm × 70 mm | 4.164 mm × 430 mm × 70 mm |
| Weight | 5.6 kg | 8.6 kg | 12.4 kg |
| Wide crosspiece | – | – | 0.9 m |
| Working height | 2.8 m | 3.85 m | 4.95 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/21/2026

Subject to change or error.