

EFA L

The safety ladder for quick application in chemical or electrical environments.

Product description

- The safety ladder for quick application in chemical or electrical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Outside width: 420 mm - particularly stable.



Hints and special features

in accordance with DIN EN 131-1, order No. 41255
includes a stabiliser bar.

Complies with EN 131 Professional.

Product features

Load capacity	Material	Pitch rung/tread	Standards	Tread depth
---------------	----------	------------------	-----------	-------------



max. 150 kg	Glass-fibre reinforced plastic	265 mm	EN 131 professional	30 mm
Type rung/tread serrated	Warranty 10 years	certification-mark-pf TÜV-SÜD		

Product variants

SKU 41251	SKU 41253	SKU 41255
Number of rungs 6	Number of rungs 10	Number of rungs 14
Overall length 1.92 m	Overall length 2.993 m	Overall length 4.16 m
Stile depth 58 mm	Stile depth 58 mm	Stile depth 73 mm
Transport dimensions 1.924 mm x 430 mm x 70 mm	Transport dimensions 3.044 mm x 430 mm x 70 mm	Transport dimensions 4.164 mm x 430 mm x 70 mm
Weight 5.6 kg	Weight 8.6 kg	Weight 12.4 kg
Working height 2.8 m	Working height 3.85 m	Wide crosspiece 0.9 m
		Working height 4.95 m