

EFA L

The safety ladder for quick application in chemical or electrical environments.

Product description

- The safety ladder for quick application in chemical or electrical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Outside width: 420 mm - particularly stable.



Hints and special features

in accordance with DIN EN 131-1, order No. 41255

includes a stabiliser bar.

Complies with EN 131 Professional.

Product features

Load capacity	Material	Pitch rung/tread	Standards	Tread depth
---------------	----------	------------------	-----------	-------------

max. 150 kg	Glass-fibre reinforced plastic	265 mm	EN 131 professional	30 mm
Type rung/tread	Warranty			
serrated	10 years			

Product variants

SKU	SKU	SKU
41251	41253	41255
Number of rungs	Number of rungs	Number of rungs
6	10	14
Overall length	Overall length	Overall length
1.92 m	2.993 m	4.16 m
Stile depth	Stile depth	Stile depth
58 mm	58 mm	73 mm
Transport dimensions	Transport dimensions	Transport dimensions
1.924 mm × 430 mm × 70 mm	3.044 mm × 430 mm × 70 mm	4.164 mm × 430 mm × 70 mm
Weight	Weight	Weight
5.6 kg	8.6 kg	12.4 kg
Working height	Working height	Wide crosspiece
2.8 m	3.85 m	0.9 m
		Working height
		4.95 m