

Saferstep LH

These flexible ladders ensure safe access to shelving and can be adapted to the required height.

Product description

- These flexible ladders ensure safe access to shelving and can be adapted to the required height.
- The shelf-mounted ladders feature two hooks for anchor rails up to 36 mm in diameter, as well as additional hooks for vertical storage on the shelf.



Hints and special features

When ordering, please specify the vertical measurement from the floor to the top edge of the pipe rail!

Complies with EN 131 Professional.



Product features

Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Tread depth	80 mm
Type rung/tread	Safer Step
Warranty	10 years

Product variants

	1041356	1041358	1041360	1041362	1041364
Height hook on vertical	=1,31m - =1,78 m	=1,79m - =2,28 m	=2,29m - =2,82 m	=2,83m - =3,35 m	=3,36m - =3,87 m
Max height hook on vertical	1.78 m	2.28 m	2.82 m	3.35 m	3.87 m
Min height hook on vertical	1.31 m	1.79 m	2.29 m	2.83 m	3.36 m
Number of treads	6	8	10	12	14
Transport dimensions	1.940 mm × 423 mm × approx. 120 mm	2.500 mm × 423 mm × approx. 120 mm	3.060 mm × 423 mm × approx. 120 mm	3.620 mm × 423 mm × approx. 120 mm	4.180 mm × 423 mm × approx. 120 mm
Weight	7 kg	10.2 kg	11.3 kg	12.5 kg	13.8 kg

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/26/2026

Subject to change or error.