



Everest 2E

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural

Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	270 mm
Standards	EN 131 professional
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Wheels	Rubber

Product variants

	40245	40246	40247	40248	40249	40214
Number of rungs	2 × 6	2 × 8	2 × 10	2 × 12	2 × 14	2 × 16
Overall length, extended	2.95 m	4.07 m	4.96 m	6.09 m	7.21 m	8.33 m
Overall length, retracted	1.83 m	2.39 m	3 m	3.56 m	4.07 m	4.7 m
Stile depth	58 mm	68 mm	68 mm	73 mm	85 mm	98 mm
Transport dimensions	1.830 mm × 500 mm × 130 mm	2.390 mm × 500 mm × 130 mm	3.000 mm × 500 mm × 140 mm	3.570 mm × 500 mm × 160 mm	4.130 mm × 500 mm × 160 mm	4.690 mm × 500 mm × 180 mm
Weight	7.6 kg	9.8 kg	13.5 kg	18 kg	19.5 kg	26.2 kg
Wide crosspiece	–	0.9 m	1 m	1.1 m	1.2 m	1.2 m
Working height	3.8 m	4.85 m	5.75 m	6.8 m	7.9 m	9 m



	40215	40216	40217
Number of rungs	2 × 18	2 × 20	2 × 24
Overall length, extended	9.13 m	10.25 m	12.22 m
Overall length, retracted	5.2 m	5.74 m	6.9 m
Stile depth	98 mm	114 mm	114 mm
Transport dimensions	5.210 mm × 500 mm × 230 mm	5.770 mm × 500 mm × 230 mm	6.900 mm × 500 mm × 230 mm
Weight	28.8 kg	33 kg	41.5 kg
Wide crosspiece	1.2 m	1.2 m	1.2 m
Working height	9.75 m	10.85 m	12.75 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.