

Everest 2E

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating	Connection Stile-Rung	External width of lower ladder	Load capacity	Material
---------	-----------------------	--------------------------------	---------------	----------

natural	flanged	490 mm	max. 150 kg	Aluminium
Pitch rung/tread 270 mm	Standards EN 131 professional	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years
Wheels Rubber	certification-mark-pf TÜV-SÜD			

Product variants

SKU 40245	SKU 40246	SKU 40247
Number of rungs 2 × 6	Number of rungs 2 × 8	Number of rungs 2 × 10
Overall length, extended 2.95 m	Overall length, extended 4.07 m	Overall length, extended 4.96 m
Overall length, retracted 1.83 m	Overall length, retracted 2.39 m	Overall length, retracted 3 m
Stile depth 58 mm	Stile depth 68 mm	Stile depth 68 mm
Transport dimensions 1.830 mm × 500 mm × 130 mm	Transport dimensions 2.390 mm × 500 mm × 130 mm	Transport dimensions 3.000 mm × 500 mm × 140 mm
Weight 7.6 kg	Weight 9.8 kg	Weight 13.5 kg
Working height 3.8 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m
	Working height	Working height

	4.85 m	5.75 m
SKU 40248	SKU 40249	SKU 40214
Number of rungs 2 × 12	Number of rungs 2 × 14	Number of rungs 2 × 16
Overall length, extended 6.09 m	Overall length, extended 7.21 m	Overall length, extended 8.33 m
Overall length, retracted 3.56 m	Overall length, retracted 4.07 m	Overall length, retracted 4.7 m
Stile depth 73 mm	Stile depth 85 mm	Stile depth 98 mm
Transport dimensions 3.570 mm × 500 mm × 160 mm	Transport dimensions 4.130 mm × 500 mm × 160 mm	Transport dimensions 4.690 mm × 500 mm × 180 mm
Weight 18 kg	Weight 19.5 kg	Weight 26.2 kg
Wide crosspiece 1.1 m	Wide crosspiece 1.2 m	Wide crosspiece 1.2 m
Working height 6.8 m	Working height 7.9 m	Working height 9 m
SKU 40215	SKU 40216	SKU 40217
Number of rungs 2 × 18	Number of rungs 2 × 20	Number of rungs 2 × 24
Overall length, extended 9.13 m	Overall length, extended 10.25 m	Overall length, extended 12.22 m



Overall length, retracted	Overall length, retracted	Overall length, retracted
5.2 m	5.74 m	6.9 m
Stile depth	Stile depth	Stile depth
98 mm	114 mm	114 mm
Transport dimensions	Transport dimensions	Transport dimensions
5.210 mm × 500 mm × 230 mm	5.770 mm × 500 mm × 230 mm	6.900 mm × 500 mm × 230 mm
Weight	Weight	Weight
28.8 kg	33 kg	41.5 kg
Wide crosspiece	Wide crosspiece	Wide crosspiece
1.2 m	1.2 m	1.2 m
Working height	Working height	Working height
9.75 m	10.85 m	12.75 m