

Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	420 mm

Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Tread depth	38 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	44834	44820	44822	44824	44826	44828
Number of rungs	2 × 8	2 × 10	2 × 12	2 × 14	2 × 16	2 × 18
Overall length, extended	3.8 m	4.93 m	6.05 m	7.17 m	8.29 m	9.17 m
Overall length, retracted	2.42 m	2.98 m	3.54 m	4.1 m	4.66 m	5.23 m
Stile depth	58 mm	68 mm	68 mm	85 mm	85 mm	85 mm
Transport dimensions	2.420 mm × 420 mm × 115 mm	2.980 mm × 430 mm × 120 mm	3.540 mm × 430 mm × 135 mm	4.100 mm × 430 mm × 135 mm	4.660 mm × 430 mm × 145 mm	5.230 mm × 430 mm × 145 mm
Weight	9.3 kg	11.3 kg	15.4 kg	17.8 kg	21.5 kg	23.9 kg
Wide crosspiece	0.8 m	0.9 m	1 m	1.1 m	1.2 m	1.2 m
Working height	4.6 m	5.65 m	6.8 m	7.85 m	8.7 m	9.8 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/29/2026

Subject to change or error.