

## Everest EFA 2E

Plastic ladder for access to great heights, for use in electrical and chemical environments.

### Product description

- Plastic ladder for access to great heights, for use in electrical and chemical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 41288-41290.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- External width of lower ladder: 420 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	73 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

## Product variants

	41288	41290	41292
Number of rungs	2 × 8	2 × 10	2 × 12
Overall length, extended	4.17 m	4.91 m	6.03 m
Overall length, retracted	2.44 m	2.95 m	3.51 m
Transport dimensions	2.500 mm × 430 mm × 125 mm	2.950 mm × 430 mm × 150 mm	3.510 mm × 430 mm × 150 mm
Weight	14.3 kg	19.5 kg	23.3 kg
Wide crosspiece	0.8 m	0.9 m	1 m
Working height	4.95 m	5.7 m	6.75 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/14/2026

Subject to change or error.