

Everest EFA 2E

Plastic ladder for access to great heights, for use in electrical and chemical environments.

Product description

- Plastic ladder for access to great heights, for use in electrical and chemical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 41288-41290.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- External width of lower ladder: 420 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

External width of lower ladder 420 mm	Load capacity max. 150 kg	Material Glass-fibre reinforced plastic	Pitch rung/tread 270 mm	Standards EN 131 professional
Stile depth 73 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	

Product variants

SKU 41288	SKU 41290	SKU 41292
Number of rungs 2 × 8	Number of rungs 2 × 10	Number of rungs 2 × 12
Overall length, extended 4.17 m	Overall length, extended 4.91 m	Overall length, extended 6.03 m
Overall length, retracted 2.44 m	Overall length, retracted 2.95 m	Overall length, retracted 3.51 m
Transport dimensions 2.500 mm × 430 mm × 125 mm	Transport dimensions 2.950 mm × 430 mm × 150 mm	Transport dimensions 3.510 mm × 430 mm × 150 mm
Weight 14.3 kg	Weight 19.5 kg	Weight 23.3 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.9 m	Wide crosspiece 1 m
Working height 4.95 m	Working height 5.7 m	Working height 6.75 m