

Skyline 2E

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

Product description

- Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.

Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Complies with EN 131 Professional.

Product features





Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread 270 mm	Standards EN 131 professional	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years
Wheels Rubber	Wide crosspiece 1.2 m			

Product variants

SKU 40206	SKU 40207	SKU 40208
Number of rungs 2 × 14	Number of rungs 2 × 16	Number of rungs 2 × 18
Overall length, extended 7.21 m	Overall length, extended 8.33 m	Overall length, extended 9.13 m
Overall length, retracted 4.14 m	Overall length, retracted 4.7 m	Overall length, retracted 5.2 m
Stile depth 85mm	Stile depth 98mm	Stile depth 98mm
Transport dimensions approx. 4.150 mm × approx. 520 mm × approx. 160 mm	Transport dimensions approx. 4.670 mm × approx. 520 mm × approx. 200 mm	Transport dimensions approx. 5.200 mm × approx. 520 mm × approx. 200 mm
Weight 23 kg	Weight 25.9 kg	Weight 32.2 kg
Working height	Working height	Working height



7.9 m	9 m	9.75 m
SKU 40209	SKU 40210	
Number of rungs 2 × 20	Number of rungs 2 × 24	
Overall length, extended 10.25 m	Overall length, extended 12.22 m	
Overall length, retracted 5.74 m	Overall length, retracted 6.9 m	
Stile depth 114mm	Stile depth 114mm	
Transport dimensions approx. 5.740 mm × approx. 520 mm × approx. 220 mm	approx. 6.910 mm × approx. 520 mm × approx. 220 mm	
Weight 33.8 kg	Weight 42.6 kg	
Working height 10.85 m	Working height 12.75 m	