

## Skyline 2E

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

### Product description

- Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Complies with EN 131 Professional.

### Product features



Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	External width of lower ladder <b>490 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Pitch rung/tread <b>270 mm</b>	Standards <b>EN 131 professional</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>
Wheels <b>Rubber</b>	Wide crosspiece <b>1.2 m</b>	certification-mark-pf <b>TÜV-SÜD</b>		

## Product variants

SKU <b>40206</b>	SKU <b>40207</b>	SKU <b>40208</b>
Number of rungs <b>2 × 14</b>	Number of rungs <b>2 × 16</b>	Number of rungs <b>2 × 18</b>
Overall length, extended <b>7.21 m</b>	Overall length, extended <b>8.33 m</b>	Overall length, extended <b>9.13 m</b>
Overall length, retracted <b>4.14 m</b>	Overall length, retracted <b>4.7 m</b>	Overall length, retracted <b>5.2 m</b>
Stile depth <b>85mm</b>	Stile depth <b>98mm</b>	Stile depth <b>98mm</b>
Transport dimensions <b>approx. 4.150 mm × approx. 520 mm × approx. 160 mm</b>	Transport dimensions <b>approx. 4.670 mm × approx. 520 mm × approx. 200 mm</b>	Transport dimensions <b>approx. 5.200 mm × approx. 520 mm × approx. 200 mm</b>
Weight <b>23 kg</b>	Weight <b>25.9 kg</b>	Weight <b>32.2 kg</b>
Working height	Working height	Working height



7.9 m	9 m	9.75 m
SKU <b>40209</b>	SKU <b>40210</b>	
Number of rungs <b>2 × 20</b>	Number of rungs <b>2 × 24</b>	
Overall length, extended <b>10.25 m</b>	Overall length, extended <b>12.22 m</b>	
Overall length, retracted <b>5.74 m</b>	Overall length, retracted <b>6.9 m</b>	
Stile depth <b>114mm</b>	Stile depth <b>114mm</b>	
Transport dimensions <b>approx. 5.740 mm × approx. 520 mm × approx. 220 mm</b>	Transport dimensions <b>approx. 6.910 mm × approx. 520 mm × approx. 220 mm</b>	
Weight <b>33.8 kg</b>	Weight <b>42.6 kg</b>	
Working height <b>10.85 m</b>	Working height <b>12.75 m</b>	