

Skyline 2E

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

Product description

- Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural



Connection Stile-Rung	flanged
External width of lower ladder	490 mm
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	270 mm
Standards	EN 131 professional
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Wheels	Rubber
Wide crosspiece	1.2 m

Product variants

	40206	40207	40208	40209	40210
Number of rungs	2 × 14	2 × 16	2 × 18	2 × 20	2 × 24
Overall length, extended	7.21 m	8.33 m	9.13 m	10.25 m	12.22 m
Overall length, retracted	4.14 m	4.7 m	5.2 m	5.74 m	6.9 m
Stile depth	85mm	98mm	98mm	114mm	114mm
Transport dimensions	approx. 4.150 mm × approx. 520 mm × approx. 160 mm	approx. 4.670 mm × approx. 520 mm × approx. 200 mm	approx. 5.200 mm × approx. 520 mm × approx. 200 mm	approx. 5.740 mm × approx. 520 mm × approx. 220 mm	approx. 6.910 mm × approx. 520 mm × approx. 220 mm
Weight	23 kg	25.9 kg	32.2 kg	33.8 kg	42.6 kg
Working height	7.9 m	9 m	9.75 m	10.85 m	12.75 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/26/2026

Subject to change or error.