

Skyline EFA 2E

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glassfibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.







Hints and special features

Complies with EN 131 Professional.

Product features

External width of lower ladder 420 mm	Load capacity max. 150 kg	Material Glass-fibre reinforced plastic	Pitch rung/tread 270 mm	Standards EN 131 professional
Stile depth 90 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	Wheels Rubber

Product variants

SKU 41274	SKU 41276
Number of rungs 2 × 14	Number of rungs 2 × 16
Overall length, extended 7.17 m	Overall length, extended 7.72 m
Overall length, retracted 4.09 m	Overall length, retracted 4.64 m
Transport dimensions 4.100 mm × 470 mm × 150 mm	Transport dimensions 4.650 mm × 450 mm × 150 mm
Weight 35.7 kg	Weight 41.3 kg
Wide crosspiece	Wide crosspiece



1.1 m	1.2 m
Working height	Working height
7.95 m	8.5 m

82362 Weilheim