



## Skyline EFA 2E

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

### Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

## Product features

Certification	TÜV-SÜD
External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	90 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Wheels	Rubber

## Product variants

	41274	41276
Number of rungs	2 × 14	2 × 16
Overall length, extended	7.17 m	7.72 m
Overall length, retracted	4.09 m	4.64 m
Transport dimensions	4.100 mm × 470 mm × 150 mm	4.650 mm × 450 mm × 150 mm
Weight	35.7 kg	41.3 kg
Wide crosspiece	1.1 m	1.2 m
Working height	7.95 m	8.5 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 6/25/2026

Subject to change or error.