

XLstep S

Designed for frequent relocation: lightweight and durable, with a wide platform, a storage tray, and sturdy ladder end caps.

Product description

- Designed for frequent relocation: lightweight and durable, with a wide platform, a storage tray, and sturdy ladder end caps.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Non-slip two-component ladder feet with a large contact surface.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Clean hands thanks to wear-resistant anodised stiles.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- Easy access up and down via sturdy 80-mm-deep treads.
- Triple-riveted connection between treads and stiles.
- 4 treads and up: High-strength polyester webbing with sewn-in attachment tabs – durable and resistant to wear and tear.
- Sturdy design for daily use: platform and profiles made of extruded aluminum.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	riveted
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	250 mm
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	42 mm
Tray	Aluminium
Tread depth	80 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	41223	41224	41225	41226	41227	41228
Anti splay	–	Belt strap	Belt strap	Belt strap	Belt strap	Belt strap
Base	0,75 m × 0,5 m	0,92 m × 0,53 m	1,08 m × 0,56 m	1,26 m × 0,59 m	1,43 m × 0,62 m	1,6 m × 0,65 m
Number of rungs, incl. platform	3	4	5	6	7	8
Overall base width	0.5 m	0.53 m	0.56 m	0.59 m	0.62 m	0.65 m



	41223	41224	41225	41226	41227	41228
Overall length	1.56 m	1.83 m	2.1 m	2.37 m	2.64 m	2.91 m
Platform height	0.74 m	0.99 m	1.24 m	1.49 m	1.74 m	1.99 m
Stile depth	42 mm	42 mm	42 mm	48 mm	48 mm	48 mm
Stile depth steps/back stay	42mm / 42mm	42mm / 42mm	42mm / 42mm	48mm / 42mm	48mm / 42mm	48mm / 42mm
Transport dimensions	approx. 1.560 mm × approx. 500 mm × approx. 155 mm	approx. 1.830 mm × approx. 530 mm × approx. 155 mm	approx. 2.100 mm × approx. 560 mm × approx. 155 mm	approx. 2.370 mm × approx. 590 mm × approx. 155 mm	approx. 2.640 mm × approx. 620 mm × approx. 155 mm	approx. 2.910 mm × approx. 650 mm × approx. 155 mm
Vertical ladder height	1.42 m	1.67 m	1.92 m	2.17 m	2.42 m	2.67 m
Weight	6 kg	6.9 kg	7.7 kg	9.1 kg	10.2 kg	11.7 kg
Working height	2.75 m	3 m	3.25 m	3.5 m	3.75 m	4 m

	41230
Anti splay	Belt strap
Base	1,94 m × 0,7 m
Number of rungs, incl. platform	10
Overall base width	0.7 m
Overall length	3.45 m
Platform height	2.49 m
Stile depth	48 mm
Stile depth steps/back stay	48mm / 42mm
Transport dimensions	approx. 3.450 mm × approx. 700 mm × approx. 155 mm
Vertical ladder height	3.17 m
Weight	14.1 kg
Working height	4.5 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 7/1/2026

Subject to change or error.