

Nova S

The sturdy classic among single-sided stepladders—ideal for a wide range of DIY projects.

Product description

- The sturdy classic among single-sided stepladders—ideal for a wide range of DIY projects.
- Spacious platform for a comfortable standing position.
- Tools and small parts are always within reach thanks to the handy storage tray.
- Easy access up and down via sturdy 80-mm-deep treads.
- 7 treads and up: High-strength polyester webbing with sewn-in attachment tabs – durable and low-wear.
- Robust design: flanged step-stile connection with a platform and extruded aluminum profiles.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged

Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	216 mm
Platform length	250 mm
Platform width	250 mm
Standards	EN 131 professional
Stile depth	48 mm
Stile depth	48 mm
Stile depth steps/back stay	48mm / 48mm
Tray	Plastic
Tread depth	80 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	42453	42454	42455	42456	42457	42458
Anti splay	–	–	–	–	Belt strap	Belt strap
Base	0,69 m × 0,42 m	0,84 m × 0,44 m	0,99 m × 0,46 m	1,14 m × 0,49 m	1,28 m × 0,51 m	1,44 m × 0,54 m
Number of rungs, incl. platform	3	4	5	6	7	8
Overall base width	0.42 m	0.44 m	0.46 m	0.49 m	0.51 m	0.54 m
Overall length	1.34 m	1.57 m	1.8 m	2.03 m	2.26 m	2.49 m
Platform height	0.61 m	0.83 m	1.05 m	1.26 m	1.48 m	1.7 m
Transport dimensions	1.350 mm × 420 mm × 120 mm	1.580 mm × 440 mm × 120 mm	1.810 mm × 470 mm × 120 mm	2.060 mm × 490 mm × 120 mm	2.270 mm × 520 mm × 120 mm	2.500 mm × 540 mm × 120 mm



	42453	42454	42455	42456	42457	42458
Vertical ladder height	1.22 m	1.43 m	1.65 m	1.86 m	2.08 m	2.29 m
Weight	4.8 kg	5.8 kg	6.9 kg	8 kg	9.1 kg	10.2 kg
Working height	2.6 m	2.85 m	3.05 m	3.25 m	3.5 m	3.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/22/2026

Subject to change or error.