

Scana S

The lightweight, anodised entry-level model for short, occasional use.

Product description

- The lightweight, anodised entry-level model for short, occasional use.
- Spacious platform for a comfortable standing position.
- Tools and small parts are always within reach thanks to the handy storage tray.
- Clean hands thanks to wear-resistant anodised stiles.
- Easy to get on and off the bus thanks to the 80-mm-deep treads.
- 6 treads and up: High-strength polyester webbing with sewn-in attachment loop – durable and low-wear.
- Optimal platform stability thanks to a sturdy extruded profile.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|-----------------------|-------------|
| Certification | TÜV-SÜD |
| Coating | anodised |
| Connection Stile-Rung | riveted |
| Load capacity | max. 150 kg |

| | |
|-----------------------------|---------------------|
| Material | Aluminium |
| Pitch rung/tread | 216 mm |
| Platform length | 250 mm |
| Platform width | 250 mm |
| Standards | EN 131 professional |
| Stile depth | 40 mm |
| Stile depth | 40 mm |
| Stile depth steps/back stay | 40mm / 40mm |
| Tray | Plastic |
| Tread depth | 80 mm |
| Type rung/tread | serrated |
| Warranty | 10 years |

Product variants

| | 44153 | 44154 | 44155 | 44156 | 44157 | 44158 |
|---------------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| Anti splay | - | - | - | Belt strap | Belt strap | Belt strap |
| Base | 0,67 m × 0,41 m | 0,82 m × 0,43 m | 0,96 m × 0,46 m | 1,1 m × 0,48 m | 1,25 m × 0,51 m | 1,7 m × 0,53 m |
| Number of rungs, incl. platform | 3 | 4 | 5 | 6 | 7 | 8 |
| Overall base width | 0.41 m | 0.43 m | 0.46 m | 0.48 m | 0.51 m | 0.53 m |
| Overall length | 1.36 m | 1.59 m | 1.82 m | 2.05 m | 2.29 m | 2.52 m |
| Platform height | 0.59 m | 0.81 m | 1.03 m | 1.24 m | 1.47 m | 1.7 m |
| Transport dimensions | 1.370 mm × 410 mm × 110 mm | 1.600 mm × 440 mm × 110 mm | 1.830 mm × 460 mm × 110 mm | 2.060 mm × 490 mm × 110 mm | 2.290 mm × 510 mm × 110 mm | 2.520 mm × 530 mm × 110 mm |
| Vertical ladder height | 1.2 m | 1.42 m | 1.64 m | 1.85 m | 2.08 m | 2.31 m |



| | 44153 | 44154 | 44155 | 44156 | 44157 | 44158 |
|----------------|--------|--------|--------|--------|--------|-------|
| Weight | 3.7 kg | 4.4 kg | 5.1 kg | 5.9 kg | 6.6 kg | 8 kg |
| Working height | 2.6 m | 2.8 m | 3 m | 3.25 m | 3.5 m | 3.7 m |

| | | |
|----------------|-------------------------|-----------------------------|
| ZARGES GmbH | Tel: +49 (0)881-687-100 | www.zarges.com |
| Zargesstraße 7 | Fax: +49 (0)881-687-500 | Effective 6/28/2026 |
| 82362 Weilheim | zarges@zarges.de | Subject to change or error. |