

Megastep B

Extreme strength in a double-sided version: 250 kg load capacity, combined with relatively low weight, for the most demanding applications.

Product description

- Extreme strength in a double-sided version: 250 kg load capacity, combined with relatively low weight, for the most demanding applications.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Clean hands thanks to wear-resistant, anodised black styles.
- Strong steel hinges.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Sturdy design: flanged rungs-to-stiles connection with extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 250 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	73 mm
Tread depth	60 mm
Type rung/tread	SL Step
Warranty	10 years

Product variants

	41189	41190	41191	41192
Base	0,93 m × 0,47 m	1,1 m × 0,5 m	1,28 m × 0,53 m	1,62 m × 0,59 m
Number of rungs	2 × 4	2 × 5	2 × 6	2 × 8
Overall base width	0.47 m	0.5 m	0.53 m	0.59 m
Overall length	1.22 m	1.5 m	1.78 m	2.34 m
Transport dimensions	1.255 mm × 480 mm × 190 mm	1.535 mm × 510 mm × 190 mm	1.815 mm × 540 mm × 190 mm	2.375 mm × 600 mm × 190 mm
Vertical ladder height	1.2 m	1.47 m	1.73 m	2.27 m
Weight	6.9 kg	8 kg	8.9 kg	11.9 kg
Working height	2.5 m	2.75 m	3 m	3.55 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/12/2026

Subject to change or error.