

Saferstep B

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	flanged

Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Tread depth	80 mm
Type rung/tread	Safer Step
Warranty	10 years

Product variants

	41303	41304	41305	41306	41307	41308
Base	0,8 m × 0,44 m	0,99 m × 0,47 m	1,18 m × 0,5 m	1,38 m × 0,53 m	1,58 m × 0,56 m	1,77 m × 0,58 m
Number of treads	2 × 3	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8
Overall base width	0.44 m	0.47 m	0.5 m	0.53 m	0.56 m	0.58 m
Overall length	0.88 m	1.16 m	1.44 m	1.72 m	2 m	2.27 m
Transport dimensions	approx. 880 mm × 445 mm × approx. 215 mm	approx. 1.160 mm × approx. 470 mm × approx. 215 mm	approx. 1.440 mm × approx. 500 mm × approx. 215 mm	approx. 1.720 mm × approx. 525 mm × approx. 215 mm	approx. 2.000 mm × approx. 560 mm × approx. 215 mm	2.275 mm × approx. 580 mm × approx. 215 mm
Vertical ladder height	0.8 m	1.06 m	1.32 m	1.58 m	1.84 m	2.1 m
Weight	4.6 kg	6.1 kg	7.6 kg	9.3 kg	10.9 kg	12.7 kg
Working height	2.3 m	2.55 m	2.8 m	3.05 m	3.3 m	3.6 m



	41310	41312	41314	41316
Base	2,16 m × 0,64 m	2,55 m × 0,7 m	2,95 m × 0,76 m	3,34 m × 0,82 m
Number of treads	2 × 10	2 × 12	2 × 14	2 × 16
Overall base width	0.64 m	0.7 m	0.76 m	0.82 m
Overall length	2.83 m	3.39 m	3.95 m	4.51 m
Transport dimensions	2.835 mm × approx. 640 mm × approx. 215 mm	3.390 mm × approx. 700 mm × approx. 215 mm	3.950 mm × approx. 765 mm × approx. 215 mm	4.510 mm × approx. 820 mm × approx. 215 mm
Vertical ladder height	2.63 m	3.16 m	3.68 m	4.21 m
Weight	16.4 kg	20.3 kg	24.4 kg	28.8 kg
Working height	4.15 m	4.65 m	5.2 m	5.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 4/2/2026

Subject to change or error.