

Comfortstep B

Padded front edges on the steps protect your shins and make working at heights for extended periods much more comfortable.

Product description

- Padded front edges on the steps protect your shins and make working at heights for extended periods much more comfortable.
- Deep treads with padded front edge for standing comfort.
- 80 mm deep treads with a padded front edge protect the shins.
- Non-slip two-component ladder feet with a large contact surface.
- Clean hands thanks to wear-resistant anodised stiles.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Durable design for everyday use: extruded aluminum profiles.
- Screwed connection between treads and stile.



Hints and special features

Maximum comfort due to padded treads.

Complies with EN 131 Professional.

Product features

Anti splay

Belt strap

Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	bolted
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	250 mm
Standards	EN 131 professional
Tread depth	80 mm
Type rung/tread	padding on front tread edges
Warranty	10 years

Product variants

	41432	41433	41434	41435	41436	41437
Base	0,75 m × 0,45 m	0,95 m × 0,48 m	1,15 m × 0,51 m	1,35 m × 0,54 m	1,55 m × 0,56 m	1,76 m × 0,59 m
Number of treads	2 × 3	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8
Overall base width	0.45 m	0.48 m	0.51 m	0.54 m	0.56 m	0.59 m
Overall length	0.84 m	1.11 m	1.38 m	1.65 m	1.92 m	2.19 m
Stile depth	42 mm	42 mm	42 mm	42 mm	42 mm	48 mm
Transport dimensions	840 mm × approx. 450 mm × 174 mm	1.110 mm × approx. 480 mm × 174 mm	1.380 mm × approx. 510 mm × 174 mm	1.650 mm × approx. 540 mm × 174 mm	1.920 mm × 560 mm × 174 mm	approx. 2.190 mm × 590 mm × 174 mm
Vertical ladder height	0.75 m	1 m	1.25 m	1.5 m	1.75 m	2 m
Weight	4.4 kg	5.8 kg	7.3 kg	8.8 kg	10.3 kg	12.2 kg
Working height	2.25 m	2.5 m	2.75 m	3 m	3.25 m	3.5 m



	41438	41430
Base	2,16 m × 0,65 m	2,36 m × 0,68 m
Number of treads	2 × 10	2 × 11
Overall base width	0.65 m	0.68 m
Overall length	2.72 m	2.99 m
Stile depth	48 mm	48 mm
Transport dimensions	2.725 mm × 650 mm × 174 mm	3.000 mm × 680 mm × 174 mm
Vertical ladder height	2.5 m	2.75 m
Weight	15.8 kg	17.6 kg
Working height	4 m	4.25 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/27/2026

Subject to change or error.