

Nova B

A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.

Product description

- A ladder that can be accessed from both sides, featuring a sturdy design intended for skilled workers with high standards.
- Stable access equipment for comfortable work at heights of up to 3.65 meters.
- Easy access up and down via sturdy 80-mm-deep treads.
- Firm positioning thanks to anti-slip plastic end caps.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Robust design: flanged step-rail connection with extruded aluminum profiles.
- Strong steel hinges.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	216 mm
Standards	EN 131 professional
Stile depth	48 mm
Tread depth	80 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	42463	42464	42465	42466	42467	42468
Base	0,6 m × 0,44 m	0,74 m × 0,47 m	0,91 m × 0,49 m	1,1 m × 0,52 m	1,27 m × 0,54 m	1,43 m × 0,56 m
Number of treads	2 × 3	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8
Overall base width	0.44 m	0.47 m	0.48 m	0.52 m	0.54 m	0.56 m
Overall length	0.68 m	0.91 m	1.15 m	1.37 m	1.61 m	1.84 m
Transport dimensions	680 mm × 440 mm × 140 mm	920 mm × 470 mm × 140 mm	1.150 mm × 490 mm × 140 mm	1.380 mm × 520 mm × 140 mm	1.610 mm × 540 mm × 140 mm	1.840 mm × 620 mm × 170 mm
Vertical ladder height	0.64 m	0.85 m	1.07 m	1.29 m	1.5 m	1.72 m
Weight	5.8 kg	8.1 kg	10.2 kg	12.4 kg	14.6 kg	16.9 kg
Working height	2.2 m	2.4 m	2.65 m	2.85 m	3.05 m	3.25 m



	42470
Base	1,78 m × 0,61 m
Number of treads	2 × 10
Overall base width	0.61 m
Overall length	2.3 m
Transport dimensions	2.300 mm × 610 mm × 140 mm
Vertical ladder height	2.15 m
Weight	21.5 kg
Working height	3.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/23/2026

Subject to change or error.