

Seventec B

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Rigid locking bar
Coating	natural
Connection Stile-Rung	riveted
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	218 mm

Standards	EN 131 professional
Stile depth	87 mm
Tread depth	85 mm
Type rung/tread	serrated
Warranty	10 years
certification-mark-pf	TÜV-SÜD

Product variants

	40353	40354	40355	40356	40357	40358
Base	0,71 m × 0,41 m	0,86 m × 0,43 m	1,02 m × 0,45 m	1,18 m × 0,47 m	1,34 m × 0,5 m	1,5 m × 0,52 m
Number of treads	2 × 3	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8
Overall base width	0.41 m	0.43 m	0.45 m	0.47 m	0.5 m	0.52 m
Overall length	0.74 m	0.97 m	1.2 m	1.43 m	1.66 m	1.9 m
Transport dimensions	740 mm × 410 mm × 230 mm	970 mm × 430 mm × approx. 230 mm	1.200 mm × 460 mm × approx. 230 mm	1.430 mm × 480 mm × 230 mm	1.660 mm × 500 mm × 230 mm	1.890 mm × 530 mm × 230 mm
Vertical ladder height	0.66 m	0.88 m	1.1 m	1.31 m	1.53 m	1.74 m
Weight	4.5 kg	6 kg	7.5 kg	9 kg	10.5 kg	12 kg
Working height	2.25 m	2.45 m	2.65 m	2.85 m	3.1 m	3.35 m

	40360
Base	1,81 m × 0,56 m
Number of treads	2 × 10
Overall base width	0.56 m
Overall length	2.35 m
Transport dimensions	2.350 mm × 580 mm × 230 mm
Vertical ladder height	2.18 m



	40360
Weight	15.5 kg
Working height	3.75 m

ZARGES GmbH	Tel: +49 (0)881-687-100	www.zarges.com
Zargesstraße 7	Fax: +49 (0)881-687-500	Effective 3/29/2026
82362 Weilheim	zarges@zarges.de	Subject to change or error.