

Coni B

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Anti-spread protection provided by two high-strength polyester webbing straps, securely attached to the rungs to prevent twisting.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	40274	40275	40311	40277	40312	40313
Base	0,78 m × 0,48 m	0,93 m × 0,51 m	1,07 m × 0,54 m	1,22 m × 0,57 m	1,36 m × 0,6 m	1,65 m × 0,66 m
Number of rungs	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8	2 × 10
Overall base width	0.48 m	0.51 m	0.54 m	0.57 m	0.6 m	0.66 m
Overall length	1.25 m	1.53 m	1.81 m	2.09 m	2.36 m	2.92 m
Stile depth	50 mm	58 mm	58 mm	58 mm	58 mm	58 mm
Transport dimensions	1.250 mm × 480 mm × 170 mm	1.530 mm × 510 mm × 170 mm	1.810 mm × approx. 540 mm × approx. 170 mm	approx. 2.090 mm × 570 mm × approx. 170 mm	approx. 2.370 mm × approx. 600 mm × approx. 170 mm	approx. 2.930 mm × approx. 660 mm × approx. 170 mm
Vertical ladder height	1.2 m	1.46 m	1.73 m	1.99 m	2.3 m	2.83 m
Weight	4.4 kg	5.8 kg	6.8 kg	7.3 kg	9 kg	11.1 kg
Working height	2.5 m	2.75 m	3 m	3.25 m	3.55 m	4.05 m



	40314	40315	40316	40320	40317
Base	1,94 m × 0,72 m	2,24 m × 0,78 m	2,54 m × 0,84 m	2,84 m × 0,9 m	3,13 m × 0,96 m
Number of rungs	2 × 12	2 × 14	2 × 16	2 × 18	2 × 20
Overall base width	0.72 m	0.78 m	0.84 m	0.9 m	0.96 m
Overall length	3.48 m	4.04 m	4.61 m	5.17 m	5.73 m
Stile depth	58 mm	62 mm	68 mm	73 mm	73 mm
Transport dimensions	approx. 3.490 mm × approx. 720 mm × approx. 170 mm	approx. 4.050 mm × approx. 780 mm × approx. 175 mm	approx. 4.610 mm × approx. 840 mm × approx. 190 mm	approx. 5.170 mm × approx. 900 mm × approx. 200 mm	approx. 5.730 mm × approx. 960 mm × approx. 200 mm
Vertical ladder height	3.37 m	3.91 m	4.45 m	5 m	5.54 m
Weight	13.3 kg	17.2 kg	21.2 kg	25.6 kg	29.8 kg
Working height	4.6 m	5.1 m	5.65 m	6.15 m	6.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/14/2026

Subject to change or error.