ZARGES

DATA SHEET

Coni B

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.



PRODUCT DESCRIPTION

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Anti-spread protection provided by two high-strength polyester webbing straps, securely attached to the rungs to prevent twisting.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.







HINTS AND SPECIAL FEATURES

Stepladder for maximum working heights of up to 6.70 m.
Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Anti splay	Belt strap
Certification	TÜV-SÜD
Coating	natural

Property	Value
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

PRODUCT VARIANTS

	40274	40275	40311	40277	40312	40313
Base	0,78 m × 0,48 m	0,93 m × 0,51 m	1,07 m × 0,54 m	1,22 m × 0,57 m	1,36 m × 0,6 m	1,65 m × 0,66 m
Number of rungs	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8	2 × 10
Overall base width	0.48 m	0.51 m	0.54 m	0.57 m	0.6 m	0.66 m
Overall length	1.25 m	1.53 m	1.81 m	2.09 m	2.36 m	2.92 m
Stile depth	50 mm	58 mm	58 mm	58 mm	58 mm	58 mm
Transport dimensions	1.250 mm × 480 mm × 170 mm	1.530 mm × 510 mm × 170 mm	1.810 mm × approx. 540 mm × approx. 170 mm	approx. 2.090 mm × 570 mm × approx. 170 mm	approx. 2.370 mm × approx. 600 mm × approx. 170 mm	approx. 2.930 mm × approx. 660 mm × approx. 170 mm
Vertical ladder height	1.2 m	1.46 m	1.73 m	1.99 m	2.3 m	2.83 m
Weight	4.4 kg	5.8 kg	6.8 kg	7.3 kg	9 kg	11.1 kg
Working height	2.5 m	2.75 m	3 m	3.25 m	3.55 m	4.05 m

	40314	40315	40316	40320	40317
Base	1,94 m × 0,72 m	2,24 m × 0,78 m	2,54 m × 0,84 m	2,84 m × 0,9 m	3,13 m × 0,96 m
Number of rungs	2 × 12	2 × 14	2 × 16	2 × 18	2 × 20
Overall base width	0.72 m	0.78 m	0.84 m	0.9 m	0.96 m
Overall length	3.48 m	4.04 m	4.61 m	5.17 m	5.73 m
Stile depth	58 mm	62 mm	68 mm	73 mm	73 mm
Transport dimensions	approx. 3.490 mm × approx. 720 mm × approx. 170 mm	approx. 4.050 mm × approx. 780 mm × approx. 175 mm	approx. 4.610 mm × approx. 840 mm × approx. 190 mm	approx. 5.170 mm × approx. 900 mm × approx. 200 mm	approx. 5.730 mm × approx. 960 mm × approx. 200 mm
Vertical ladder height	3.37 m	3.91 m	4.45 m	5 m	5.54 m
Weight	13.3 kg	17.2 kg	21.2 kg	25.6 kg	29.8 kg
Working height	4.6 m	5.1 m	5.65 m	6.15 m	6.7 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 14



Bucket hook
SKU 40115



Fastening chain
SKU 40252



Ground spikes
SKU 40939



Hook-on platform
SKU 40450



Hook-on tool box
SKU 40920



Horizontal stabiliser bar for retrofitting
SKU 41348 · 41400 · 41401



Ladder holder, lockable
SKU 40998



Pivot foot with rubber tread 100 x 55 mm
SKU 40997



Pivot foot with rubber tread 125 x 50 mm
SKU 40226



Stile extension
SKU 40922



Tension strap
SKU 40960



Theft protection
SKU 8210



Toolbag
SKU 40300



Toolbag
SKU 40301

SPARE PARTS 8



Antistatic plug-in end cap
SKU 824321



Bracing
SKU 820816



End cap
SKU 824160 · 824152 · 824165 · +2



Hinge
SKU 809021



Plug-in end cap
SKU 824347 · 824350 · 824486 · +2



Push-on end cap, antistatic
SKU 824475 · 824282 · 824283



Splay prevention (belt strap)
SKU 829729 · 827613 · 827675 · +4



User instructions label
SKU 800606

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/12/2026
Subject to change or error.