

## Coni B

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

### Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Anti-spread protection provided by two high-strength polyester webbing straps, securely attached to the rungs to prevent twisting.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

### Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Standards	EN 131 professional
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

## Product variants

	40274	40275	40311	40277	40312	40313
Base	0,78 m × 0,48 m	0,93 m × 0,51 m	1,07 m × 0,54 m	1,22 m × 0,57 m	1,36 m × 0,6 m	1,65 m × 0,66 m
Number of rungs	2 × 4	2 × 5	2 × 6	2 × 7	2 × 8	2 × 10
Overall base width	0.48 m	0.51 m	0.54 m	0.57 m	0.6 m	0.66 m
Overall length	1.25 m	1.53 m	1.81 m	2.09 m	2.36 m	2.92 m
Stile depth	50 mm	58 mm	58 mm	58 mm	58 mm	58 mm
Transport dimensions	1.250 mm × 480 mm × 170 mm	1.530 mm × 510 mm × 170 mm	1.810 mm × approx. 540 mm × approx. 170 mm	approx. 2.090 mm × 570 mm × approx. 170 mm	approx. 2.370 mm × approx. 600 mm × approx. 170 mm	approx. 2.930 mm × approx. 660 mm × approx. 170 mm
Vertical ladder height	1.2 m	1.46 m	1.73 m	1.99 m	2.3 m	2.83 m
Weight	4.4 kg	5.8 kg	6.8 kg	7.3 kg	9 kg	11.1 kg
Working height	2.5 m	2.75 m	3 m	3.25 m	3.55 m	4.05 m



	40314	40315	40316	40320	40317
Base	1,94 m × 0,72 m	2,24 m × 0,78 m	2,54 m × 0,84 m	2,84 m × 0,9 m	3,13 m × 0,96 m
Number of rungs	2 × 12	2 × 14	2 × 16	2 × 18	2 × 20
Overall base width	0.72 m	0.78 m	0.84 m	0.9 m	0.96 m
Overall length	3.48 m	4.04 m	4.61 m	5.17 m	5.73 m
Stile depth	58 mm	62 mm	68 mm	73 mm	73 mm
Transport dimensions	approx. 3.490 mm × approx. 720 mm × approx. 170 mm	approx. 4.050 mm × approx. 780 mm × approx. 175 mm	approx. 4.610 mm × approx. 840 mm × approx. 190 mm	approx. 5.170 mm × approx. 900 mm × approx. 200 mm	approx. 5.730 mm × approx. 960 mm × approx. 200 mm
Vertical ladder height	3.37 m	3.91 m	4.45 m	5 m	5.54 m
Weight	13.3 kg	17.2 kg	21.2 kg	25.6 kg	29.8 kg
Working height	4.6 m	5.1 m	5.65 m	6.15 m	6.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/30/2026

Subject to change or error.