



## EFA B

For flexible applications in electrical or chemical environments and for working under voltage.

### Product description

- For flexible applications in electrical or chemical environments and for working under voltage.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Anti splay	Belt strap
Certification	TÜV-SÜD
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

## Product variants

	41261	41256	41257	41258	41260
Base	1,08 m × 0,48 m	1,31 m × 0,54 m	1,66 m × 0,6 m	2,01 m × 0,66 m	2,7 m × 0,78 m
Number of rungs	2 × 4	2 × 6	2 × 8	2 × 10	2 × 14
Overall base width	0.48 m	0.54 m	0.6 m	0.65 m	0.77 m
Overall length	1.32 m	1.88 m	2.44 m	3 m	4.12 m
Transport dimensions	1.350 mm × 480 mm × 162 mm	1.900 mm × 540 mm × 162 mm	2.460 mm × 600 mm × 162 mm	3.000 mm × 660 mm × 160 mm	4.150 mm × 770 mm × 160 mm
Vertical ladder height	1.27 m	1.82 m	2.35 m	2.89 m	3.95 m
Weight	7.5 kg	10.5 kg	13.8 kg	17 kg	24.6 kg
Working height	2.6 m	3.1 m	3.65 m	4.15 m	5.2 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

[zarges@zarges.de](mailto:zarges@zarges.de)

[www.zarges.com](http://www.zarges.com)

Effective 6/27/2026

Subject to change or error.