



EFA B

For flexible applications in electrical or chemical environments and for working under voltage.

Product description

- For flexible applications in electrical or chemical environments and for working under voltage.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features



Anti splay	Belt strap
Certification	TÜV-SÜD
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	41261	41256	41257	41258	41260
Base	1,08 m × 0,48 m	1,31 m × 0,54 m	1,66 m × 0,6 m	2,01 m × 0,66 m	2,7 m × 0,78 m
Number of rungs	2 × 4	2 × 6	2 × 8	2 × 10	2 × 14
Overall base width	0.48 m	0.54 m	0.6 m	0.65 m	0.77 m
Overall length	1.32 m	1.88 m	2.44 m	3 m	4.12 m
Transport dimensions	1.350 mm × 480 mm × 162 mm	1.900 mm × 540 mm × 162 mm	2.460 mm × 600 mm × 162 mm	3.000 mm × 660 mm × 160 mm	4.150 mm × 770 mm × 160 mm
Vertical ladder height	1.27 m	1.82 m	2.35 m	2.89 m	3.95 m
Weight	7.5 kg	10.5 kg	13.8 kg	17 kg	24.6 kg
Working height	2.6 m	3.1 m	3.65 m	4.15 m	5.2 m



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.