

EFAmix B

The ideal, particularly lightweight solution for work in electrical and chemical environments.

Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Tread depth	60 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	41165	41166	41167	41168	41169	41170
Base	0,96 m × 0,48 m	1,13 m × 0,51 m	1,31 m × 0,54 m	1,81 m × 0,6 m	2,17 m × 0,66 m	2,55 m × 0,72 m
Number of rungs	2 × 4	2 × 5	2 × 6	2 × 8	2 × 10	2 × 12
Overall base width	0.47 m	0.5 m	0.53 m	0.59 m	0.65 m	0.71 m
Overall length	1.34 m	1.62 m	1.9 m	2.46 m	3.02 m	3.58 m
Transport dimensions	1.344 mm × 480 mm × 162 mm	1.625 mm × 510 mm × 162 mm	1.904 mm × 540 mm × 162 mm	2.464 mm × 600 mm × 162 mm	3.024 mm × 660 mm × 162 mm	3.584 mm × 720 mm × 162 mm
Vertical ladder height	1.29 m	1.55 m	1.82 m	2.33 m	2.86 m	3.38 m
Weight	7.8 kg	9.6 kg	11.4 kg	14.8 kg	18.8 kg	22.5 kg
Working height	2.6 m	2.85 m	3.1 m	3.65 m	4.15 m	4.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.