

## EFAmix B

The ideal, particularly lightweight solution for work in electrical and chemical environments.

### Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti splay	Belt strap
Certification	TÜV-SÜD

Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Tread depth	60 mm
Type rung/tread	serrated
Warranty	10 years

## Product variants

	41165	41166	41167	41168	41169	41170
Base	0,96 m × 0,48 m	1,13 m × 0,51 m	1,31 m × 0,54 m	1,81 m × 0,6 m	2,17 m × 0,66 m	2,55 m × 0,72 m
Number of rungs	2 × 4	2 × 5	2 × 6	2 × 8	2 × 10	2 × 12
Overall base width	0.47 m	0.5 m	0.53 m	0.59 m	0.65 m	0.71 m
Overall length	1.34 m	1.62 m	1.9 m	2.46 m	3.02 m	3.58 m
Transport dimensions	1.344 mm × 480 mm × 162 mm	1.625 mm × 510 mm × 162 mm	1.904 mm × 540 mm × 162 mm	2.464 mm × 600 mm × 162 mm	3.024 mm × 660 mm × 162 mm	3.584 mm × 720 mm × 162 mm
Vertical ladder height	1.29 m	1.55 m	1.82 m	2.33 m	2.86 m	3.38 m
Weight	7.8 kg	9.6 kg	11.4 kg	14.8 kg	18.8 kg	22.5 kg
Working height	2.6 m	2.85 m	3.1 m	3.65 m	4.15 m	4.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/27/2026

Subject to change or error.