

# Skymaster X

Convertible to take on challenging tasks with greater safety.

## Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged

Load capacity	max. 150 kg
Material	Aluminium
Pitch rung/tread	265 mm
Rigid locking bar	on one side
Standards	EN 131 professional
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

## Product variants

	41536	41537	41538	41539	41540	41542
Ladder length as 3-part single ladder	4.1 m	5 m	5.8 m	6.7 m	6.9 m	8.6 m
Length as 2-part single ladder and as stepladder with push-on section	3 m	3.6 m	4.1 m	4.7 m	4.95 m	6.1 m
Number of rungs	3 × 6	3 × 7	3 × 8	3 × 9	3 × 10	3 × 12
Overall length, retracted	1.9 m	2.2 m	2.45 m	2.7 m	3 m	3.55 m
Stile depth	68 mm	68 mm	73 mm	85 mm	85 mm	98 mm
Transport dimensions	1.880 mm × 500 mm × 180 mm	2.160 mm × 500 mm × 180 mm	2.440 mm × 500 mm × 200 mm	2.730 mm × 500 mm × 200 mm	3.010 mm × 500 mm × 210 mm	3.590 mm × 500 mm × 230 mm
Weight	13.8 kg	15 kg	17.5 kg	20 kg	25.2 kg	30.1 kg
Wide crosspiece	0.8 m	0.9 m	1 m	1.1 m	1.1 m	1.2 m
Working height as 3-part single ladder	5 m	5.8 m	6.65 m	7.45 m	7.7 m	9.35 m



	41544
Ladder length as 3-part single ladder	9.7 m
Length as 2-part single ladder and as stepladder with push-on section	6.95 m
Number of rungs	3 × 14
Overall length, retracted	4.15 m
Stile depth	98 mm
Transport dimensions	4.140 mm × 500 mm × 230 mm
Weight	37.9 kg
Wide crosspiece	1.2 m
Working height as 3-part single ladder	10.4 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 4/6/2026

Subject to change or error.