

Varioflex B

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

Product description

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Ideal for applications in difficult terrain.

Complies with EN 131 Professional.

Product features

Additional adjustment range on ladder section 0.4 m	Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium
Pitch rung/tread	Tread depth	Type rung/tread	Warranty	



265 mm

30 mm

serrated

10 years

Product variants

SKU	SKU
41936	41938
Additional adjustment range on support section	Additional adjustment range on support section
1.3 m	1.85 m
Length excluding extension	Length excluding extension
1.8 m	2.35 m
Number of rungs	Number of rungs
2 × 6	2 × 8
Transport dimensions	Transport dimensions
1.850 mm × 600 mm × 140 mm	2.410 mm × 650 mm × 140 mm
Weight	Weight
12.5 kg	15.5 kg
Working height	Working height
3 m	3.55 m