

Varioflex B

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

Product description

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Ideal for applications in difficult terrain.

Complies with EN 131 Professional.

Product features

Additional adjustment range on ladder section	0.4 m
Coating	natural
Connection Stile-Rung	flanged
Load capacity	max. 150 kg



Material	Aluminium
Pitch rung/tread	265 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years

Product variants

	41936	41938
Additional adjustment range on support section	1.3 m	1.85 m
Length excluding extension	1.8 m	2.35 m
Number of rungs	2 × 6	2 × 8
Transport dimensions	1.850 mm × 600 mm × 140 mm	2.410 mm × 650 mm × 140 mm
Weight	12.5 kg	15.5 kg
Working height	3 m	3.55 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.